

ALL-SEASON Transmission/ Differential Oil J20D



Description/Benefits

- Recommended for equipment with common transmission, hydraulic, final drive and wet brake sump where intermixing may occur due to implement attachment.
- Specially designed for low temp performance
- Outstanding frictional properties provide chatter free operation of wet brakes.
- Protects gears, pumps and other parts from wear due to high loads.
- Prolongs life of oil seals, hydraulic hoses and other rubber parts.
- Keeps all system parts clean and varnish free for smooth operation.

Applications

- Commercial Tractor Fluid-Low Viscosity is recommended for use in agricultural tractors, certain makes and models of construction equipment and particular hydraulic systems where the manufacturer recommends:
- John Deere J20D, J20B, –Low Vis Hy-Guard
- Versatile HyGear Fluid, Spec 23,24m
- Case/IH Hy-Tran Ultra SSL FLUID
- New Holland MasterTran SSL
- Ford* M2C134 A,B,C,D,
- Kubota* UDT*



Premium Performance. Heavy Duty Value.

- Caterpillar* TO-2* (Obsolete)
- Massey-Ferguson M-1127A-1141
- *Intended for low temperature applications as
- recommended by these OEM's.

Performance Specification

Specification	J20D
Viscosity, cSt @ 40°C	33.6
Viscosity, cSt @ 100°C	7.3
Viscosity Index	191
Brookfield Viscosity @ -20°C	1,280
Brookfield Viscosity @ -40°C	15,900
Flash Point, °C	325
Pour Point, °C	-48
API Gravity Kg/L	0.875