

LEAD
THE
FIELD.

DXT Grain Carts



Harvest Hauler.

The Brandt DXT dual-auger grain cart delivers the perfect combination of unload speed, large carrying capacity, and unmatched durability fit for your operation. With capacities of 1,150 to 2,500 bushels and unloading speeds of up to 1,000 bu/min, these grain carts meet the rigorous demands of a fast paced harvest.

① Easier To Operate

Get a fast and complete cleanout on every unload with features that make operation efficient:

- Tank design has industry-leading tank angles and a full-length cleanout door with minimal obstruction points.
- Ground-level access door ensures quick and safe entry into the tank.
- Pivoting vertical auger enables adjustment of the spout height between 9' 5" and 16' 6" from ground level.

② More Versatile

Dual auger design is available in the right size and configuration for any harvest setup:

- All models are purpose-built with a low center of gravity for added in-field stability, with loading side heights as low as 10'.
- Configure your cart with the auger size and unload side (right or left) that best suits your operational needs.
- Choose from high flotation, walking tandem, or steerable tandem tire configurations. Or, to reduce compaction, upgrade to Brandt Tracks.

③ Total Reliability

Heavy-duty, low-maintenance design ensures a premium quality fit that your operation can depend on:

- The new gearbox driven design delivers reliable transfer of power to both augers with an unobstructed sump for efficient grain flow.
- Two-speed fold cylinder and oversized cast hinge components deliver extended auger fold cycling with a spring loaded top auger bearing to ensure a snug connection at the 6-tooth auger coupler.
- Precision formed and robotically welded frame components are optimized to handle loaded weights and stress.

Powerful Value. **Delivered.**

Brandt

DXT Grain Carts

Specifications

	1150DXT		1350DXT		1600DXT		2000DXT		2500DXT	
General										
Capacity (bushels)	1,150		1,350		1,600		2,000		2,500	
Recommended HP	225		250		300		400		500	
Unload Speed (bu/min)	850/1000		850/1000		850/1000		850/1000		850/1000	
Horizontal Auger Diameter	20"		20"		20"		20"		20"	
Vertical Auger Diameter	22" or 24"		22" or 24"		22" or 24"		22" or 24"		22" or 24"	
Auger Flighting	1/2" Extended Life									
4-Direction Spout Travel	Side to Side 117°, Fwd/Bkwd 39°									
Auger Tilt Angle	37° to 63°		37° to 63°		37° to 63°		37° to 63°		37° to 63°	
Undercarriage										
	Tires		Tracks		Tires		Tracks		Tracks	
Standard Tire/Track Size*	IF1050/50R32	130" x 36"	IF1250/50R32	130" x 36"	IF900/60R32 CFO	150" x 36"	IF900/60R32 CFO	170" x 36"	170" x 36"	170" x 36"
Tire Load Index	195	n/a	201	n/a	182	n/a	182	n/a	n/a	n/a
Axle Spindle Diameter	5.5"	5.5"	5.5"	5.5"	4.5"	5.5"	4.5"	5.5"	5.5"	5.5"
Weight										
Empty (lbs)	22,666	26,637	27,368	27,114	28,846	30,720	33,470	38,171	38,997	38,997
Tongue - Empty / Full (lbs)	4,356 / 4,449	4,356 / 4,449	4,988 / 6,729	4,988 / 6,729	3,180 / 4,336	3,180 / 4,336	5,139 / 5,398	5,139 / 5,398	5,938 / 5,842	5,938 / 5,842
Dimensions										
Ground Clearance	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"
Overall Cart Height	11' 5"	11' 5"	12' 6"	12' 6"	12' 6"	12' 6"	12' 5"	12' 5"	12' 5"	12' 11"
Side Heights	10' 0" / 11' 0"	10' 0" / 11' 0"	11' 1" / 12' 1"	11' 1" / 12' 1"	11' 1" / 12' 1"	11' 1" / 12' 1"	11' 0" / 12' 0"	11' 0" / 12' 0"	11' 0" / 12' 0"	11' 5" / 12' 5"
Overall Cart Length	31' 6"	31' 6"	30' 3"	30' 3"	33' 11"	33' 11"	37' 9"	37' 9"	37' 9"	42' 9"
Wheelbase	19' 4"	19' 4"	19' 4"	19' 4"	20' 9"	20' 9"	23' 2"	23' 2"	23' 2"	24' 9"
Tank Width	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	13' 9"	13' 9"	13' 9"	13' 10"
Overall Cart Width	12' 6"	13' 0"	13' 7"	13' 0"	13' 7"	13' 0"	14' 3"	14' 3"	14' 3"	14' 3"
Auger Reach										
Side – Spout Down	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	9' 8"	9' 8"	9' 8"	9' 8"
Side – Max	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	10' 5"	10' 5"	10' 5"	10' 5"
Height – Spout Down	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"
Height – Max	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"

*Multiple tire and track sizes available

Features

Superior Powder-Coat Paint

Reduces tank friction to improve cleanout.

Extended Life Auger Flighting

With 1/2" thick wear edges for max longevity.

Easy Hookup

With hose management arm, color coded couplers, and optional hydraulic jack.

Easy Operation of the Auger

With one-touch auger fold, auger height and four-direction spout adjustment with joystick controls.

Five-Point Load Cell System

With double-ended shear beams that are the most accurate and versatile weighing system available with easy access to mounting.

Hitch Mounted Suspension

Delivers a smoother ride for the operator while reducing wear and tear on the cart and tractor.

Minimal Maintenance

With six regular grease points throughout the design.

Scan to learn more.



Contact Us

Call: 1-866-4-BRANDT
Email: agriculture@brandt.ca
Or visit: www.brandt.ca

