

	1150DXT			1350DXT			1600DXT		2000DXT		2500DXT
<b>General</b>											
Capacity (bushels)	1,150			1,350			1,600		2,000		2,500
Recommended Horsepower	225			250			300		400		500
Unload Speed (bu/min)	850/1000			850/1000			850/1000		850/1000		850/1000
Horizontal Auger Diameter	20"			20"			20"		20"		20"
Vertical Auger Diameter	22" or 24"			22" or 24"			22" or 24"		22" or 24"		22" or 24"
Flighting	1/2" Extended Life			1/2" Extended Life			1/2" Extended Life		1/2" Extended Life		1/2" Extended Life
4-Direction Spout Travel	Side to Side 136°, Fwd/Bkwd 37°			Side to Side 136°, Fwd/Bkwd 37°			Side to Side 136°, Fwd/Bkwd 37°		Side to Side 136°, Fwd/Bkwd 37°		Side to Side 117°, Fwd/Bkwd 39°
Auger Tilt Angle	37° to 63°			37° to 63°			37° to 63°		37° to 63°		37° to 63°
<b>Undercarriage</b>											
	<b>Tires</b>	<b>Walking Tandem</b>	<b>Brandt Tracks</b>	<b>Tires</b>	<b>Walking Tandem</b>	<b>Tracks</b>	<b>Steering Tandem</b>	<b>Tracks</b>	<b>Steering Tandem</b>	<b>Tracks</b>	<b>Tracks</b>
Tire/Track size	IF1050/50R32 LSW1100/45R46 IF1250/50R32	520/85R42 650/85R42	36" x 130" 36" x 150"	IF1250/50R32	520/85R42 650/85R42	36" x 130" 36" x 150"	IF900/60R32 CFO	36" x 150"	IF900/60R32 CFO	36" x 170"	36" x 170"
Axle Spindle Diameter	5.5"	4.5"	5.5"	5.5"	4.5"	5.5"	4.5"	5.5"	4.5"	5.5"	5.5"
<b>Weight</b>											
Empty (lb)	22,666	24,714	26,637	27,368	27,883	27,114	28,846	30,720	33,470	38,171	38,997
Tongue - Empty (lb)	4,356	4,356	4,356	4,988	4,988	4,988	3,180	3,180	5,139	5,139	5,938
Tongue - Full (lb)	4,449	4,449	4,449	6,729	6,729	6,729	4,336	4,336	5,398	5,398	5,842
<b>Dimensions</b>											
A - Ground Clearance	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"	1' 5"
B - Overall Cart Height	11' 5"	11' 5"	11' 5"	12' 6"	12' 6"	12' 6"	12' 6"	12' 6"	12' 5"	12' 5"	12' 11"
C - Loading Side Height	10'	10'	10'	11' 1"	11' 1"	11' 1"	11' 1"	11' 1"	11'	11'	11' 5"
D - Non-Loading Side Height	11'	11'	11'	12' 1"	12' 1"	12' 1"	12' 1"	12' 1"	12'	12'	12' 5"
E - Overall Cart Length	31' 6"	31' 6"	31' 6"	30' 3"	30' 3"	30' 3"	33' 11"	33' 11"	37' 9"	37' 9"	42' 9"
F - Wheelbase	19' 4"	19' 4"	19' 4"	19' 4"	19' 4"	19' 4"	20' 9"	20' 9"	23' 2"	23' 2"	24' 9"
G - Tank Width	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	11' 10"	13' 9"	13' 9"	13' 10"
H - Overall Cart Width	12' 6"	12' 3"	13'	13' 7"	12' 3"	13'	13' 7"	13'	14' 3"	14' 3"	14' 3"
<b>Auger Reach</b>											
I - Side - Spout Down	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	10' 3"	9' 8"	9' 8"	9' 8"
J - Side - Max	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"	10' 5"	10' 5"	10' 5"
K - Height - Spout Down	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"	9' 3" - 15' 11"
L - Height - Max	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"	16' 10"

**For more information**  
 Call us at 1-866-4-BRANDT  
 Email us at agriculture@brandt.ca  
 Or visit us at www.brandt.ca

**Brandt Agricultural Products**  
 PO Box 317, 13th Avenue & Pinkie Road  
 Regina, SK, Canada  
 S4P 3A1

