

**LEAD  
THE  
FIELD.**

## Top-Drive Field GrainBelts



### A Soft Touch in a Tough Business.

Brandt's 15LP Top-Drive Field GrainBelts give you the edge you need, delivering high-volume performance with a powerful combination of speed, gentleness, and versatility. Engineered to get the job done quickly and carefully, Brandt conveyors protect your seed investment and maintain grain quality, all while moving up to 6,500 bu/hr.

#### ① Performance Boost

Get better performance with gentle handling:

- The optimized intake and transition increases grain-flow efficiency to achieve peak performance in varying conditions.
- Capacity is optimized to match bin unload systems up to 6,500 bu/hr on a 10hp electric motor, increasing efficiency.
- The optional wrap roller increases the contact area of the belt on the drive roller for more consistent traction and performance.

#### ② Maximum Versatility

Achieve ultimate product retention with these versatile machines:

- The double lip intake seal keeps your crop on the belt where it belongs, increasing product retention while loading.
- Lowest clearance intake hoppers (8") with retractable hopper fabric that extends up 16" for accessing lower bin unload systems.
- Belt wipers in the intake and discharge keep the return side of the belt free from debris and build-up, reducing uneven wear and tear on the belt and drive components.

#### ③ Easy To Operate

The user-friendly design reduces maintenance costs while promoting operator safety:

- Brandt's EZTRAK tensioning and tracking system keeps your belt aligned and properly tensioned at all times. And, the visual tension indicator makes it easy to see when adjustment is needed.
- The enclosed wind guard delivers environmental protection and operator safety.
- The pre-wired switchbox and plug electric drives allow for setup-free operation.

Powerful Value. **Delivered.**

**Brandt**

# TOP-DRIVE FIELD GRAINBELTS

## SPECIFICATIONS

	1535TD	1545TD
<b>Performance</b>		
Capacity (bushels per hour)	6,500	6,500
Recommended Horsepower - Electric	7.5 - 10	7.5 - 10
<b>Dimensions</b>		
Belt Width	15"	15"
Conveyor Length	37'	47'
Raised Height	17' 5"	23'
Raised Reach	13' 5" Electric / 15' Hydraulic	16' 9" Electric / 18' 11" Hydraulic
Lowered Reach	15' Electric / 17' 3" Hydraulic	20' 3" Electric / 23' 1" Hydraulic
Transport Height (hitch at 12")	10' 7"	11' 8"
Transport Length	40' 5"	48' 1"
Intake Reach	11' 11" Electric / 9' 6" Hydraulic	12' Electric / 9' 1" Hydraulic
Wheel Track Width	94"	94"
Total Weight	1,720 lb	2,030 lb
Tube Diameter	10"	10"
Tire Size	ST205/75D15	ST205/75D15
<b>Features</b>		
Lift Mechanism	Manual Winch	Manual Winch
Windguards	Standard	Standard
Drive System	Top-Drive	Top-Drive
<b>Hopper</b>		
Hopper Style	Low Profile	Low Profile
Hopper Width and Length	36" x 60"	36" x 60"
Collapsed Hopper Height	8"	8"
Extended Hopper Height	16"	16"

## OPTIONS

### Weight transfer kit

to prevent upending the conveyor

### Electric or hydraulic drive option

to suit your operational needs

For more information  
 Call us at 1-866-4-BRANDT  
 Email us at [agriculture@brandt.ca](mailto:agriculture@brandt.ca)  
 Or visit us at [www.brandt.ca](http://www.brandt.ca)

**Brandt Agricultural Products**  
 PO Box 317, 13th Avenue & Pinkie Road  
 Regina, SK, Canada  
 S4P 3A1

