

# Portable Productivity.

The all-new Brandt A-Series Grain Decks are portable grain pits designed to boost your harvest productivity. Eliminate the need to position a hopper multiple times under a trailer—simply drive over the conveyor to unload and get back to the field faster.

### **1** Higher Productivity

The drive-over conveyor delivers the performance needed to save you time when unloading trucks:

- Choose between 20" models that move up to 15,000 bu/hr or 24" models capable of up to 18,500 bu/hr.
- Trucks and low trailers can easily clear the 5 <sup>3</sup>/<sub>4</sub> inch deck height (6 <sup>3</sup>/<sub>4</sub>" with ramp extensions).
- Proven EZMOVE system is operator friendly for fast and easy positioning of your Grain Deck.

### Increased Uptime

The rugged design of the drive-over conveyor is purpose built to keep you working and worry free:

- The hopper (38" x 115") provides easy unloading, while the deck (7' x 12') ensures space for any truck and trailer.
- The patented EZTRAK tensioning and tracking system keeps your belt aligned and tensioned properly.
- Double-Lip Intake Sealing System all but eliminates leakage behind the belt; belt wiper extends belt life.

### **3** Lower Operating Cost

The Grain Deck is built with proven and reliable components to deliver an excellent return on investment:

- Gentle on pulses and seed, reducing impact damage caused by common grain handling systems.
- Needs less horsepower than conventional augers, making it compatible with a wider range of tractors.
- Enclosed belts and drive system deliver operator safety and superior protection against the elements.



Powerful Value. Delivered.

# **20 & 24 Series Grain Decks** Specifications

# Options

	2010A	2015A	2410A	2415A
Performance				
Bushels per hour*	Up to 15,000	Up to 15,000	Up to 18,500	Up to 16,500
HP (Electric)	15	15	15	15
HP (Gas)	40	40	40	40
Hydraulic Requirements (gpm)	14-20	14-20	20-26	20-26
Weight (lbs)				
Gas Engine w/ EZMOVE	4232	4416	4416	4600
Hydraulic Drive w/o EZMOVE	3840	4024	4024	4208
Hydraulic Drive w/o EZMOVE	3188	3372	3372	3556
Hitch Weight	940-1340	940-1340	940-1340	940-1340
Dimensions				
Belt Width	20"	20"	24"	24"
Tube Length	10'	10'	15'	15'
Discharge Height (to bottom of spout)	32 ¾"	53 ¼"	39 ¼"	59 ¾"
Discharge Reach	69"	125 ½"	90"	146 ½"
Deck Width	67 ¾"	67 ¾"	67 ¾"	67 ¾"
Hopper (W x L)	34" x 115"	34" x 115"	42" x 115"	42" x 115"
Deck Width w/Ramp Extensions	84 ¾"	84 ¾"	84 ¾"	84 ¾"
Total length w/o EZMOVE	28' 8¾"	33' 6¼"	30' 7¾"	35' 4"
Total length w/ EZMOVE	31' 2¾"	35'10½"	33' 1¼"	37' 9½"

#### Hydraulic/ Electric/ Gas Drive

#### EZMOVE

#### **Ramp Extensions**

#### **Bunker Kit**

The Bunker Kit allows you to convert the Grain Deck and a Brandt Harvest Grain Belt to move in unison at 90° to your grain pile while operating with the tractor.

#### **Oilseed-certified System**

Safely use the Grain Deck with oilseeds, such as canola. The specialized V-Belt, additional seal kits, and roller-guarding protects the unit from excess material buildup in the event of oil exposure.

Scan to learn more.



**Contact Us** Call: 1-866-4-BRANDT Email: agriculture@brandt.ca Or visit: www.brandt.ca

9 Brandt Industries Ltd. All rights reserved. The Brandt name and logo are trademarks of Brandt Industries Ltd., used under license. All product information and specifications are subject to change without notification. Printed in Canada. Revised 11/2024-CU

