

FEATURES

Low-profile Gooseneck

Delivers more space for maximum payload and optimized mounting for air and electrical connections. Simple, mechanical connection is more robust and easily connects to the trailer on uneven ground.

Abrasion-resistant Paint

Maximizes trailer life and resale value with the industry's most durable powder-coat finish.

14 HP EFI Engine

Delivers 57% faster flow-rate than the competition while maintaining maximum lift capacity. Save time and money with faster starts, reduced downtime, and better fuel economy.

Longer Standard Knuckle Trough

Allows your excavator to sit 5" lower and could save you an over-height permit.

Five-position Ride Height Valve

Easily adjusts to varying terrain.

Increased Fifth-wheel Slide

Delivers 7' of fifth-wheel adjustment enables the jeep to accommodate a wider variety of equipment.

Built-in Lift Points on End Ramps

Allows you to easily remove ramps with a forklift and sling.

Remote Air Tank Drain-valves

Saves you valuable time on maintenance.

Unlimited Neck Shimming

Utilizes spring-loaded shim legs with extra stroke, making it easy and safe to add or remove shims.

Rebound-limiting Chains

Protect the shocks so your equipment lasts longer.

Individual Suspension Shut-off

Extends tire life by lifting an axle when travelling empty.

Wide Stinger

Delivers improved stability when removing the gooseneck.

Optional Features

- Auto-Shim Spreader/Pin-On Axle Booster
- Pin-on 4th Axle
- Brandt V10 Slingshot Booster
- Removable Rear Fenders
- Lift Kit for 3rd and/or 4th Axle
- Steel Swing-out Outriggers
- Removable Deck End Ramps
- Drop Side Deck


Work Ready

Brandt Trailers


60-Ton Highway Trailers

60-TON HIGHWAY TRAILER DIMENSIONS


H600 + Auto-Shim Spreader



H600 + PM10 Pin-On Axle



H600 + V10 Booster



TRAILER **H600** JEEP **R40** PIN-ON AXLE **PM10** BOOSTER **V10**

60-TON HIGHWAY TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

1 year standard comprehensive and 1 year extended warranty with 5 year structural at no additional cost. Ask us for details.

FLEXIBLE FINANCING

Custom financing solutions available to best suit your business. Ask us for details.

Haul It All.

The H600 multi-axle heavy haul trailer gives you the flexibility to haul it all, from standard to specialized loads, with ease.

① Easier to Own

Our team is here to support you every step of the way and make owning the H600 hassle-free with:

- Flexible in-house purchasing options including rentals, leasing, and conventional financing are available to suit your financing needs.
- Brandt's advanced paint protection provides better longevity and corrosion protection to keep your trailer looking like new for longer.
- Reliable design with long-lasting components lowers the total cost of ownership.

② Easier to Operate

You deserve a trailer that works as hard as you do. That's why we optimized the H600 with:

- Simple, robust gooseneck connection that gets you on the road faster, even in rough terrain.
- Five-position ride height valve is included standard and can quickly adapt to suit any road conditions.
- Brandt's industry-leading 14HP EFI powerpack delivers maximum lift capacity at a higher flow rate to save you time and money.

③ Safer to Own

Safety is critical on the jobsite, and the H600 is designed with features that maximize operator protection, including:

- Extra-stroke shim legs that eliminate pinch points allow shims to be added or removed safely when adjusting the deck height.
- Rugged, built-in lift points on the end ramps ensure risk-free ramp removal.
- Remotely mounted air tank drain valves make completing daily maintenance faster and easier.

For more information
Call us at 1-888-227-2638
Email us at sales@brandt.ca
Or visit us at brandt.ca/trailers

© Brandt Industries Ltd. All rights reserved. The Brandt name and logo are trademarks of Brandt Industries Ltd., used under license. All product information and specifications are subject to change without notification. Printed in Canada. Revised 09/2024-CU



Powerful Value. **Delivered.**



SPECIFICATIONS H600 TRAILER

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY			
Rated Load on 16' (ton)	60		
Nominal Axle Wall Thickness (in)	3/4		
DURABILITY - STRUCTURE			
Decking/Floor Material	3" Fir		
Paint Finish	Zinc Primer + Polyester Powder Coat		
DIMENSIONS			
Deck Length (ft)	24	26	
Overall Length (ft)	52'11"-54'11" Tridem	56'3"-58'3" Quad	
Wheelbase (ft) - 88" KP	41'11"-43'11" Tridem	41'7"-42'7" Quad	
Deck Width (ft)	8'6"	9	10
Axle Spacing (in)	54	60	
Running Gear Width (ft)	8'6"	9	10
Loaded Deck Height (in)	22" at 6" Ground Clearance		
Loaded Ground Clearance (in)	Adjustable 5 Settings: 6.5" - 9.5"		
Upper Coupler Height (in)	50		
Gooseneck Swing (in)	88, 112, 154, 172 w/ GN Ext.		
GOOSENECK FEATURES			
Hydraulic Actuated, Spring Loaded Shim Block	<input checked="" type="radio"/>		
Gooseneck Extension for Tandem Jeep	<input type="radio"/>		
Aluminum Fenders, Removable Back 1/3	<input type="radio"/>		
Hydraulic Flip Kit	<input type="radio"/>		
Swingout Lights	<input type="radio"/>		
Work Lights	<input type="radio"/>		
Dual Source Hydraulics - 14HP EFI Engine, Wet Kit Diverter Valve	<input type="radio"/>		
Low Profile Neck	<input checked="" type="radio"/>		

DECK FEATURES			
Low Profile Front Loading Ramps	<input checked="" type="radio"/>		
D-Rings on Front Loading Ramps, Inside & Outside	<input checked="" type="radio"/>		
Chain Pockets Every 4' on Outside of Web	<input checked="" type="radio"/>		
8 Internal Chain Pockets	<input checked="" type="radio"/>		
Knuckle Trough - Last 6' of Deck	<input checked="" type="radio"/>		
Full Deck Knuckle Trough	<input type="radio"/>		
2 Formed Wire Mesh Chain Baskets	<input checked="" type="radio"/>		
Pin Joint Connection to Rear Frame, Includes Built in Shims	<input checked="" type="radio"/>		
Clip in Outriggers Every 2'	<input type="radio"/>		
2 Pairs of Swingout Lights	<input type="radio"/>		
Bolt in Slip Resistant Knuckle Trough Cover	<input type="radio"/>		
Lockable Aluminum Storage Box Lid	<input type="radio"/>		
Removable Deck End Ramps	<input type="radio"/>		
Bolted Rubber Belting on Decking	<input type="radio"/>		
6' Deck Extension	<input type="radio"/>		
Deck Extension Outriggers	<input type="radio"/>		
Bolt in Slip Resistant Deck Extension Trough Cover	<input type="radio"/>		

SUSPENSION FRAME FEATURES			
Suspension Style	Tridem	Quad	
Drum Brakes	<input checked="" type="radio"/>		
PAN22 Disc Brakes	<input type="radio"/>		
8.25 X 22.5" Aluminum Wheels	<input type="radio"/>		
275/70R22.5 Michelin X MLT Z Highway Tires	<input type="radio"/>		
Rebound Limiters & Air Bag Shutoffs	<input checked="" type="radio"/>		
Removable HMW Fenders	<input type="radio"/>		
Battery Back-up Kit for Strobes	<input type="radio"/>		
Slip Resistant Boom Trough Cover	<input type="radio"/>		
Remote Drain Valve Accessible on Outside of Frame	<input checked="" type="radio"/>		
Load Bearing Bolsters with Chain Pockets	<input checked="" type="radio"/>		
Mudflaps	<input checked="" type="radio"/>		
5 Position Ride Height Valve	<input checked="" type="radio"/>		
Strobe Lights	<input checked="" type="radio"/>		

EASY TO OWN - PURCHASE OPTIONS

Cash, Rent or Lease*, Low Rate Lease*	<input type="radio"/>
---------------------------------------	-----------------------

PEACE OF MIND - WARRANTY

1 Year - Comprehensive Bumper to Bumper	<input checked="" type="radio"/>
2 Year - Comprehensive Bumper to Bumper	<input type="radio"/>
3 Year - Comprehensive Bumper to Bumper	<input type="radio"/>

Included at no extra cost Option available *See Dealer for Details

R40 JEEP

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY	
Rated Load (ton)	40
Nominal Axle Wall Thickness (in)	5/8
DURABILITY - STRUCTURE	
Paint Finish	Zinc Primer + Polyester Powder Coat
DIMENSIONS	
Overall Length (ft)	26'6"
Wheelbase (ft)	19'3"
Running Gear Width (ft)	8'6"
Loaded 5th Wheel Height (in)	53
Upper Coupler Height (in)	50
Axle Spacing (in)	49
5th Wheel Travel (in)	94
Tractor Swing Clearance (in)	79/100
Jeep Swing (in)	168

GOOSENECK FEATURES

Aluminum Fenders, Including Mudflap	<input type="radio"/>
Spare Tire Carrier	<input type="radio"/>
Hydraulic Lines for Wet Kit Connection	<input type="radio"/>

MAIN FRAME FEATURES

Premium 2 Speed Landing Gear	<input checked="" type="radio"/>
Brake Release Valve	<input checked="" type="radio"/>
Suspension Dump Valve	<input checked="" type="radio"/>
Suspension Air Gauge	<input checked="" type="radio"/>
Weatherproof Lid to House Air Valves	<input checked="" type="radio"/>
Remote Drain Valve Accessible on Outside of Frame	<input checked="" type="radio"/>
Mudflaps	<input checked="" type="radio"/>
Chain Pockets for Lifting	<input checked="" type="radio"/>

SUSPENSION FRAME FEATURES

Drum Brakes	<input checked="" type="radio"/>
PAN22 Disc Brakes	<input type="radio"/>
8.25 X 22.5" Aluminum Wheels	<input checked="" type="radio"/>
275/70R22.5 Bridgestone M840 On/Off Road Tires	<input type="radio"/>
Rebound Limiters & Air Bag Shutoffs	<input checked="" type="radio"/>
Rear Ramps Accommodate Mechanical Gooseneck Trailers	<input checked="" type="radio"/>

EASY TO OWN - PURCHASE OPTIONS

Cash, Rent or Lease*, Low Rate Lease*	<input type="radio"/>
---------------------------------------	-----------------------

PEACE OF MIND - WARRANTY

1 Year - Comprehensive Bumper to Bumper	<input checked="" type="radio"/>
2 Year - Comprehensive Bumper to Bumper	<input type="radio"/>
3 Year - Comprehensive Bumper to Bumper	<input type="radio"/>

Included at no extra cost Option available *See Dealer for Details

PM10 PIN-ON AXLE

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY			
Capacity (ton)	10		
Use With	C550, H600		
DIMENSIONS			
Overall Length (ft)	5'4"		
Running Gear Width (ft)	8'6"	9	10
Interaxle Spacing (in)	54	60	
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin		
MAIN FRAME			
Main Frame Type	No Hassle Flip Lugs, Load Bearing Front Bolster & Lightbar		
Beams	Fabricated, 100 ksi Flanges & Webs		
Load Securement	2 Pair of D-Rings for Flipping or Tie-Down		
Suspension Capacity	(1) x HT250 25,000 lb		
Axle Capacity (Nominal)	22,500 lb per axle, 5/8 wall		
Hubs	Duralite, 75W90 Synthetic Gear Oil, 10-Stud		
Air System	FMVSS, CMVSS Compliant, Common Air Operation, Remote Air Tank Drain Valves		
Electrical System	FMVSS, CMVSS Compliant, LED Lighting, 4" Bumper Mounted Strobes with Switch in Control Box, OEM Weatherseal Harnessing		

AUTO-SHIM SPREADER

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY	
Capacity (ton)	10
Use With	C550, H600
DIMENSIONS	
Overall Length (ft)	10'4"
Interaxle Spacing (in)	14'7"
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin, Top Hook for Easy Connection
MAIN FRAME	
Main Frame Type	Center Spine, Vertical Frame Pivot for Steering
Beams	Fabricated, 100 ksi Flanges & Webs
Shim Method	Automatic Shim, Automatic Relief
Electrical System	Strobes with Switch in Control Box, OEM Weatherseal Harnessing

Included at no extra cost Option available *See Dealer for Details

V10 BOOSTER

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY	
Capacity (ton)	10
Use With	C550, H600, H650, H750
DIMENSIONS	
Overall Length (ft)	13'
Running Gear Width (ft)	8'6"
Interaxle Spacing (in)	14'1"
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin, Top Hook for Easy Connection
MAIN FRAME	
Main Frame Type	Center Spine, Vertical Frame Pivot for Steering
Beams	Fabricated, 100 ksi Flanges & Webs
Load Securement	2 Pair of D-Rings for Flipping or Tie-Down
Suspension Capacity	25,000 lb
Axle Capacity (Nominal)	22,500 lb per axle, 5/8 wall
Hubs	Duralite, 75W90 Synthetic Gear Oil, 10-Stud
Shim Method	Manual Shimming
Air System	FMVSS, CMVSS Compliant, Weather Sealed Air Controls Including Suspension Air Gauge, Common Air for HT250 Suspension and Regulated Air Override Suspension Settings, Spring Brake Release Valve, Remote Air Tank Drain Valves
Electrical System	FMVSS, CMVSS Compliant, LED Lighting, 4" Bumper Mounted Strobes with Switch in Control Box, Control Box Lighting, OEM Weatherseal Harnessing, Rear 7-way Socket for Auxiliary Lighting

Included at no extra cost Option available *See Dealer for Details