

	216A HP	221A HP	326A HP	331A HP	338A HP	341A HP	345A HP
Performance							
Working Width	15' 10"	20' 9"	26' 8"	31' 6"	37' 4"	41' 10"	45'
Max Working Depth	8" with 20" discs and 9" with 22" discs						
Horsepower Requirement	200 - 320	250 - 420	300 - 520	350 - 620	400 - 620+	500 - 620+	620+
Weight (lbs)	17,810	20,685	27,664	28,905	31,924	37,234	38,960
Transport							
Hitch Weight (lbs)	5,343	6,206	8,299	8,672	9,577	11,170	11,688
Width	9' 11"	9' 11"	14' 5"	14' 5"	14' 5"	17' 8"	17' 8"
Height (Max)	12' 8"	12' 8"	12' 4"	12' 4"	12' 4"	13'	13'
Discs							
Number of Discs	38	50	62	74	90	98	106
Disc Angle	14° Front Gang and 17° Rear Gang						
Disc Spacing	5"	5"	5"	5"	5"	5"	5"
Suspension	4 x 40mm Argus Rubber Torsion per disc arm						
Disc Sizes	20" or 22"	20" or 22"	20" or 22"	20" or 22"	20" or 22"	20" or 22"	20" or 22"
Disc Options	Smooth, U-notched, Fluted						
Rear Finishing							
Rear Finishing Attachments	Rubber Roller, 12-Bar Cage (Basket) Roller, Spring Roller						
Rear Finishing Suspension	Option						
Hydraulically Adjustable Scrapers	Option (Rubber Roller Only)						
Cylinders							
Transport Cylinder(s)	6" x 2" x 40" (1)	6" x 2" x 40" (1)	6" x 2" x 40" (2)	6" x 2" x 40" (2)	6" x 2" x 40" (2)	6.5" x 2.5" x 42" (2)	6.5" x 2.5" x 42" (2)
Wing Cylinders	4" x 2" x 20"	4" x 2" x 20"	4" x 2" x 20"	4" x 2" x 20"	4" x 2" x 20"	4" x 2" x 28"	4" x 2" x 28"
Cart Wheel Cylinders	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"
Wing Wheel Cylinders	n/a	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"
Wing Roller Cylinders	4.25" x 2" x 8"	4.25" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"	3.75" x 2" x 8"
Center Roller Cylinders	n/a	n/a	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"	4.25" x 2" x 8"
Tires							
Transport	550/45R22.5 (16 ply)	550/45R22.5 (16 ply)	600/50R22.5 (16 ply)	600/50R22.5 (16 ply)	600/50R22.5 (16 ply)	750/45R22.5 (16 ply)	750/45R22.5 (16 ply)
Wing	n/a	400/60R15.5 (16 ply)	550/45R22.5 (16 ply)	550/45R22.5 (16 ply)	550/45R22.5 (16 ply)	600/50R22.5 (16 ply)	600/50R22.5 (16 ply)

For more information

Call us at 1-866-4-BRANDT
 Email us at agriculture@brandt.ca
 Or visit us at www.brandt.ca

Brandt Agricultural Products

PO Box 317, 13th Avenue & Pinkie Road
 Regina, SK, Canada
 S4P 3A1