

	UBE518 LOW-PROFILE FLATBED		UBE720 LOW-PROFILE FLATBED			
	PERFORMANCE	PERFORMANCE GALVANIZED	PERFORMANCE	PERFORMANCE GALVANIZED	PREMIUM	PREMIUM GALVANIZED
<b>RELIABILITY - RATED CAPACITY</b>						
GVWR (lb)	9900		14,900			
Rated Payload (lb)	7050	7000	11,600	11,550	11,250	11,200
Tongue Weight (lb)	1250		1860			
Suspension	Torsion - Bolt On		Torsion - Bolt On			
Axle Rating (lb)	2 x 5200		2 x 7000			
<b>DURABILITY - STRUCTURE</b>						
HSS Mainframe Size (in)	6		8			
Decking Material	Premium Fir		Premium Fir			
Surface Finish	Powder Top Coat, Polyester JD Grey	<b>Galvanized</b>	Powder Top Coat, Polyester JD Grey	<b>Galvanized</b>	Powder Top Coat, Polyester JD Grey	<b>Galvanized</b>
<b>DIMENSIONS</b>						
Total Length (ft)	24.7		26.9	27.2		
Fixed Deck Length (ft)	16		18			
Dovetail Length (ft)	2		2			
Deck Width (in) – inside fender to fender	82		82			
Deck Height (in)	21		22			
<b>INCLUDED EQUIPMENT</b>						
Pull Type	Bumper		Bumper			
Jackleg Wind Type – top or side	Top		Side			
Jackleg Speeds	Single		Single			
Jackleg Lift Capacity (lb)	7000		10,000			
Steel Tread Plate Fenders – bolt on	●		●			
Black Steel Wheels	●		●			
Wheel Size	15" Rim - 6K - 6 Stud - 5.5" Circle		16" Rim - 6K - 8 Stud - 6.5" Circle			
Tire Size	ST225/75R15 LRE		ST235/80R16 LRE			
Premium Radial 10 ply Tires – speed rated to 120 kph	●		●			
<b>EASY TO OPERATE - SAFETY &amp; CONVENIENCE FEATURES</b>						
Spring Assist Flip Up Ramps – 2 x 5'	●		●			
Spring Assist Full-Width Bi-Folding Ramps – 40 x 60"			●			
Dual Chains c/w hook latches – 36"	●		●			
Steel Tread Plate Fenders – bolt on	●		●			
Premium Protected Wiring	●		●			
Breakaway Switch – includes LED test lights, battery & charger	●		●			
Integral Footholds	●		●			
Tier 1 LED Lighting System	●		●			
Forward Self-Adjusting Brakes	●		●			
E-Z Lube Grease Axle Bearings	●		●			
Load Bearing Toolbox	○		●			
<b>ACCESSORIES</b>						
Coupler Lock	○		○			
Wheel Locks	○		○			
JD Link – fleet tracking	○		○			