

LEAD
THE
FIELD.

10HP Swing Away Augers



Full Speed Ahead.

The 10HP Swing Away Auger from Brandt reduces truck unload times to get you back to the field even faster during busy harvest seasons. And, these augers are available in 60', 70', and 80' lengths to deliver ultimate versatility. The 10HP model is the ideal combination of high capacity, reliability, and ease of use that you need to get the job done.

① Faster Speeds

Brandt Swing Away Augers are faster than ever to ensure you get more done in less time:

- The innovative HP technology feeds the 10" main flighting with the 11" swing flighting to achieve a capacity of up to 7,200 bu/hr.
- The low-clearance 70" x 40" hopper makes positioning under trailer hoppers easier than ever. And, it features flat-free tires for trouble-free use during harvest.
- The EZSWING hopper mover is available with electronic controls to guarantee easy maneuvering with a remote control or the LeadHand mobile app.

② Longer Lasting

Depend on your auger to serve you well for many seasons:

- Brandt's extended-life auger flighting is thicker at the edges where the most wear typically occurs to keep your auger running longer and more efficiently.
- The heavy-duty scissor lift delivers maximum reach, clearance, and low transport height while the standard monotube undercarriage improves safety, stability, and product life.
- Quick and easy access to the gearbox, u-joints, and the ability to reverse the auger allows for a complete cleanout.

③ Easier Maintenance

Protect your investment and increase resale value with Brandt's innovative design:

- Two robust easy-access clean-out doors on the transition ensure easy maintenance. And, the transition spout is sealed completely to keep your product in and moisture out.
- Designed with a chain coupler between the swing tube flighting and the gearbox for worry-free maintenance. The coupler absorbs shocks and protects the gearbox, increasing its longevity.
- Brandt's superior powder-coat paint optimizes cleanout, rust protection, and component life to increase your resale value.

Powerful Value. **Delivered.**

Brandt

10HP Swing Away Augers

Specifications

	1060HP	1070HP	1080HP
Performance			
Capacity (bushels per hour)	7,200	7,200	7,200
Recommended Horsepower	95	105	115
Dimensions			
Tube Diameter	10"	10"	10"
Length	60'	70'	80'
Height – Lowered / Raised	9' 8" / 42'	11' / 48' 6"	11' 6" / 52' 9"
Reach – Lowered / Raised	25' 6" / 16' 6"	35' 6" / 22' 6"	42' 8" / 30'
Transport Length	62' 3"	72' 2"	82' 2"
Transport Height	12' 4"	12' 6"	13' 6"
Wheel Track Width	11' 10"	11' 10"	11' 10"
Tube Thickness	13 ga	13 ga	13 ga
Flighting – Main / Swing Away	3/16" / 3/8"	3/16" / 3/8"	3/16" / 3/8"
Core Diameter	2"	2"	2"
Lower Bearing Size	1-3/8"	1-3/8"	1-3/8"
Gearbox Shaft Diameter	1-1/4"	1-1/4"	1-1/4"
Hitch Weight (lbs)	500	850	850
Total Weight (lbs)	3,460	3,600	4,380
Undercarriage			
Lift Mechanism	Scissor	Scissor	Scissor
Frame Arms	6" x 8" x 3/16"	6" x 8" x 3/16"	6" x 8" x 1/4"
Axle	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"
Hydraulic Cylinder Size	3.5" x 30"	4" x 30"	4.5" x 30"
Number of Hydraulic Cylinders	1	1	1
Hydraulic Requirements (psi)	1,600	1,400	1,400
Tire Size	ST205/75R15	ST205/75R15	ST235/75R15
Tire Ply Rating	6 Ply	6 Ply	8 Ply
Self-Leveling Swing Away Hopper			
Length x Width x Height	70" x 40" x 10"	70" x 40" x 10"	70" x 40" x 10"
Height w/ Extension	17"	17"	17"
# of Horizontal Flights	2	2	2
# of Wheels	4	4	4
Wheel Size	10"	10"	10"

Options

Man/Hyd/Elec Winch

Man/Hyd/Elec EZSWING Hopper Mover

Right-angle Drive

Reversing Kit

Plastic Bucket Spout

No-snag Bucket Spout

Hopper Cover

Safety Light Kit

Work Light Kit

Scan to learn more.



Contact Us

Call: 1-866-4-BRANDT
 Email: agriculture@brandt.ca
 Or visit: www.brandt.ca

