



STRAIGHT BODY | MAX BODY™  
**UBD814** | **UBD816 / UGD816**  
**DUMP TRAILERS**



**INDUSTRY BEST WARRANTY**

**2 YEAR WARRANTY**

Unmatched Two-Year Bumper-to-Bumper Warranty on all components. Five-Year Structural Warranty. *Ask us for details.*

**FLEXIBLE FINANCING**

Custom financing solutions available to best suit your business. *Ask us for details.*

HITCH TYPE	GVWR	BODY LENGTH	RATED PAYLOAD
<b>PowerPin™ Ball, Gooseneck</b>	<b>16,000 – 17,500 lb</b>	<b>14 Feet, 16 Feet</b>	<b>10,088 – 11,294 lb</b>

**All Muscle. No Flex.**

Tough jobs call for even tougher trailers. Brandt Work Ready™ dump trailers are built with high-rigidity rectangular tube frames that minimize trailer flex under heavy loads to outlast the competition.

**① Easier to Own**

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Extensive coast-to-coast dealer network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

**② Easier to Operate**

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Two-way gate, barn door, or two-way hydraulic gate ramp options are available, allowing the trailer to be optimized for the task at hand.
- Torsion spring suspension system delivers reliable shock-absorption without requiring any maintenance work.

**③ Safer**

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Power Pin™ ball hitch is specially designed to prevent binding, ensuring that the trailer is properly secured to the towing vehicle, every single time.
- Safety prop-rod secures the box in the raised position, maximizing operator safety while performing maintenance on the trailer.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.

Powerful Value. **Delivered.**



# DUMP TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UBD814 Tandem Straight Body			UBD816 Tandem Max Body™		UGD816 Tandem Max Body™	
	PERF	PREM	PLAT	PERF	PREM	PERF	PREM
<b>Base Unit Key Specifications</b>							
<b>RELIABILITY - RATED CAPACITY</b>							
GVWR (lb)	16,000			16,000		17,500	
Payload (lb)	10,846	10,605	10,575	10,421	10,088	11,294	10,893
Axle Type – bolt on	Torsion			Torsion		Torsion	
Axle Rating (lb)	2 x 7000			2 x 7000		2 x 7000	
<b>DURABILITY - STRUCTURE</b>							
HSS Mainframe Size (in)	8			8		8+3	
Decking/Floor Material	10 Gauge Steel			10 Gauge Steel		10 Gauge Steel	
Surface Finish	Polyurethane Primer + Hi-Gloss Polyurethane Paint or Hot-Dipped Galvanized Finish						
Side Height and Material – if applicable	18" - 10 Gauge Steel			21.75" - 10 Gauge Steel		21.75" - 10 Gauge Steel	
<b>DIMENSIONS</b>							
Total Length (ft)	20.3	20.84	20.9	22.3	26	25.38	25.94
Body Length (ft)	14			16		16	
Deck Width (in) – inside fender to fender	82			82/97.2		82/97.2	
Deck/Floor Height (in) – unloaded/loaded	25.3/23			25.3/23		25.3/23	
<b>INCLUDED EQUIPMENT</b>							
Hitch Type	PowerPin™ Ball - 2½"			PowerPin™ Ball - 2½"		Gooseneck	
Jackleg Wind Type – top or side	Side			Side		Side	
Jackleg Lift Capacity (lb)	20,000			20,000		20,000	
Gate Type	2-way	Combo	2-way	2-way	Combo	2-way	Combo
Main Hydraulic Damping or Dump Hoist Cylinder(s)	6" - 3200 psi - 15" Stroke						
HPU Type – P=power up/down, G=gravity down	P/G	P/G	P	P/G		P/G	
Wheel Size	16" rim - 8 stud - 6.5" circle			16" rim - 8 stud - 6.5" circle		16" rim - 8 stud - 6.5" circle	
Tire Size	ST235/80R16 LRE			ST235/80R16 LRE		ST235/80R16 LRE	
<b>EASY TO OPERATE - SAFETY &amp; CONVENIENCE FEATURES</b>							
Dual Chains c/w hook latches – 36"	●			●		●	
Four 4" D-Rings	●			●		●	
Arctic Cold Weather Wiring	●			●		●	
Breakaway Switch – includes LED test lights, battery & charger	●			●		●	
Rear Stabilizer Jacks				●			
Tier 1 LED Lighting System	●			●		●	
Premium Radial 10 ply Tires – speed rated to 120 kph	●			●		●	
Forward Self-Adjusting Brakes	●			●		●	
EZ-Lube Grease Axle Bearings	●			●		●	
Heavy Duty Toolbox	●			●		●	
Safety Prop Rod	●			●		●	
110V Shore Charging Plug In	●			●		●	
Bucket Shelf – Max Body™ Models				●		●	
Black Steel Wheels	●	●		●		●	
Aluminum Spoke Wheels	○	○	●	○		○	
Steel Tread Plate Fenders – bolt on	●			●		●	
<b>ADDITIONAL FEATURES</b>							
Michels Premium Mesh Tarp	●			●		●	
Side Board Brackets	●			○		○	
Mud Flaps	○	○	●	○		○	
Spare Tire Carrier	○	○	●	○		○	
Spare Tire on Standard Steel Wheel	○	○	●	○		○	
Spare Tire on Aluminum Spoke Wheel			●				
Additional Premium Rockguard on Front Facing Surfaces			●				
HD Charge Kit	○			○		○	
Hydraulic Jack	○			○		○	
Wireless Pump Remotes	○			○		○	

AVAILABLE ACCESSORIES: Bumper Pull/Pintle/Gooseneck Locks, Wheel Locks, JDLink™ (fleet tracking), 12V High Amp Charging Cable and Wireless Remote  
 ● Included at no extra cost ○ Option available